



# TLC-1000-U2S

## USB2.0

### HD PTZ Video Camera

Telycam TLC-1000-U2S is cost effective 10X USB2.0 HD video conferencing PTZ camera for web conferencing and video conferencing, to offer enterprise-class image and flexible control.



## FEATURES

- ◆ Adopted advanced industrial level ISP, and Sony 5MP CMOS sensor, to output crisp image
- ◆ Full HD 1080p/30 resolution
- ◆ WDR, BLC, 3D noise reduction and exposure compensation value to be adjustable via OSD menu with applied environment
- ◆ Fast & accurate focus and 10x lossless optical zoom, with 62.5 degree wide angle FOV, along with smooth pan/tilt rotation to capture any view in conferencing space
- ◆ Plug&Play USB2.0 video streaming output, compatible with most leading video conferencing software: Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux. ect, at different operation system Windows, Mac, Android and Linux."
- ◆ FECC (Far End Camera Control) supported
- ◆ Standard Visca and UVC1.5 Protocol
- ◆ PTZ control and firmware upgrade via RS232 (RS485) and USB
- ◆ 128 presets.



Telecam Technology Co.,Ltd  
 New Add.: 6F, Building A, Shuanghuan Information Technology Industrial Park, No.8,  
 Baoqing Rd, Longgang District, Shenzhen, 518116, China  
 TEL: 0086-755-33275155 Http://www.telycam.com www.telecamtech.com

# TECHNICAL SPEC

<b>Camera</b>			
<b>Sensor</b>	1/2.8 inch high quality 5MP HD CMOS sensor		
<b>Frame Rate</b>	1920x1080p30/25, 1280x720p60/50/30/25		
<b>Video Format</b>	MJPEG		
<b>Lens Zoom</b>	10x optical zoom		
<b>Focal length</b>	f=4.7 (wide)~47mm(tele)		
<b>View Angle</b>	6.43° (wide) ~ 62.5° (tele)		
<b>SNR</b>	>50dB		
<b>Noise Reduction</b>	2D/3D		
<b>Minimum Lux</b>	0.1 lux		
<b>White Balance</b>	Auto / Manual		
<b>Focus</b>	Auto / Manual		
<b>Iris</b>	Auto / Manual		
<b>Electronic Shutter</b>	Auto / Manual		
<b>BLC</b>	Auto / Manual		
<b>Mechanism</b>			
<b>Pan Rotation Angle</b>	-170° ~ +170°	<b>Tilt Rotation Angle</b>	-35° ~ +90°
<b>Pan Rotation Speed</b>	0°~120°/s	<b>Tilt Rotation Speed</b>	0°~80°/s
<b>Preset</b>	128 presets via RS232, 10 presets via remote controller		
<b>Control</b>	RS232/RS485/USB/Remote Controller		
<b>Video Port</b>	USB2.0		
<b>Input voltage</b>	DC12V		

Camera Dimension  
148mm×132mm×161mm

Package Dimension  
28x24x24cm

Package Content

Camera, Remote Controller  
RS232 cable, USB2.0 cble,  
Power Supply

