



# TLC-300-U2S USB2.0

## HD PTZ Video Camera

Telycam TLC-300-U2S is an affordable price as well as professional quality USB2.0 HD PTZ Video Conferencing Camera , sensible choice for cost effective unified video collaboration solution



## FEATURES

- ◆ Adopted advanced American Ambarella ISP, and Sony 5MP CMOS sensor, to output crisp image
- ◆ Full HD 1080p/30 resolution
- ◆ WDR, BLC, 3D noise reduction and exposure compensation value to be adjustable via OSD menu with applied environment
- ◆ Fast&accurate focus and 12x lossless optical zoom, with 72.5 degree wide angle FOV, along with smooth pan/tilt rotation to capture any view in conferencing space
- ◆ Plug&Play,USB2.0 video streaming output, compatible with most leading video conferencing software: Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ FECC (Far End Camera Control) supported
- ◆ PTZ control and firmware upgrade via RS232 (RS485) and USB
- ◆ 128 presets
- ◆ Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



Telecam Technology Co.,Ltd  
New Add.: 6F, Building A, Shuanghuan Information Technology Industrial Park, No.8,  
Baoqing Rd, Longgang District,Shenzhen,518116,China  
TEL: 0086-755-33275155 [Http://www.telycam.com](http://www.telycam.com) [www.telecamtech.com](http://www.telecamtech.com)

# TLC-300-U2S

## USB2.0

### HD PTZ Video Camera



## TECHNICAL SPEC

<b>Sensor</b>	1/2.8 inch high quality 5MP HD CMOS sensor	<b>Frame Rate</b>	1920x1080@30, 1280x720@30, 640x480@30
<b>Video Format</b>	MJPEG	<b>Lens Zoom</b>	12x optical zoom
<b>Focal length</b>	f=3.92(wide)~47.32mm(tele)	<b>View Angle</b>	6.3° (wide) ~ 72.5° (tele)
<b>SNR</b>	>50dB	<b>Noise Reduction</b>	2D/3D
<b>Minimum Lux</b>	0.1 lux	<b>White Balance</b>	Auto / Manual
<b>Focus</b>	Auto / Manual	<b>Iris</b>	Auto / Manual
<b>Electronic Shutter</b>	Auto / Manual	<b>BLC</b>	Auto / Manual
<b>Mechanism</b>			
<b>Pan Rotation Angle</b>	-170° ~ +170°	<b>Tilt Rotation Angle</b>	-35° ~ +90°
<b>Pan Rotation Speed</b>	0°~120°/s	<b>Tilt Rotation Speed</b>	0°~80°/s
<b>Preset</b>	128 presets via RS232, 10 presets via remote controller	<b>Control</b>	RS232/RS485/USB/Remote Controller
<b>Video Port</b>	USB2.0	<b>Input voltage</b>	DC12V

Camera Dimension

220mm×173mm×117mm

Package Dimension

32x30x31cm

Package Content

Camera, Remote Controller,

RS232 cable, USB2.0 cble,

Power Supply

