



TLC-300-U3

HD Video Camera

TLC-300-U3 Professional-grade dual HDMI&USB3.0 HD PTZ Video Camera is adopted Ambarella A9 ISP, and Sony 1/2.3" 12MP sensor, to output unparalleled image quality, applied in both cloud-based and on-premise video collaboration solution for corporation, education, government



FEATURES

- ◆ Crystal clear, noiseless and realistic color image with full details
Full HD 1080p/60 (59.94) video streaming
- ◆ WDR, BLC, 3D noise reduction and exposure compensation features to adjustable via OSD menu
- ◆ DVI-I(HDMI)&USB3.0 output simultaneously
- ◆ Enable it works for cloud-based unified communication as well as on premise video collaboration with major software: Zoom.us, Skype4business, Vido, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ Fast&accurate focus and 12x lossless optical zoom, with 72.5 degree wide angle FOV, along with smooth pan/tilt rotation capture any view in conferencing space
- ◆ Standard Sony Visca and UVC1.5 protocol, RS232/RS485/USB PTZ control and firmware upgrade
- ◆ 128 presets
- ◆ Max 7 cameras daisy chain.
- ◆ Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



Telecam Technology Co.,Ltd
 New Add.: 6F, Building A, Shuanghuan Information Technology Industrial Park, No.8,
 Baoqing Rd, Longgang District, Shenzhen, 518116, China
 TEL: 0086-755-33275155 [Http://www.telycam.com](http://www.telycam.com) www.telecamtech.com

TECHNICAL SPEC

Camera			
Sensor	1/2.3 inch high quality 12MP HD CMOS sensor		
Frame Rate	DVI-I output: 1080p59.94/50/29.97/25; 720p59.94/50/29.97/25 USB3.0 output: 1080p59.94/50/29.97/25;720p59.94/50/29.97/25		
Video Format	YUY2		
Lens Zoom	12x optical zoom		
Focal length	f= 3.92(wide)~47.32mm(tele)		
View Angle	6.3° (wide) ~ 72.5° (tele)		
SNR	>50dB		
Noise Reduction	2D/3D		
Minimum Lux	0.01 lux		
White Balance	Auto / Manual		
Focus	Auto / Manual		
Iris	Auto / Manual		
Electronic Shutter	Auto / Manual		
BLC	Auto / Manual		
Mechanism			
Pan Rotation Angle	-170° ~ +170°	Tilt Rotation Angle	-35° ~ +90°
Pan Rotation Speed	0°~120°/s	Tilt Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller		
Control	RS232/RS485/USB/Remote Controller		
Video Port	DVI-I , USB3.0		
Input voltage	DC12V		

Camera Dimension
220mm×173mm×117mm

Package Dimension
32x30x31cm

Package Content
Camera, Remote Controller,
RS232 cable, USB3.0 cable,
Power Supply

