



TLC-300-U3S USB3.0 HD PTZ Video Camera

Telycam TLC-300-U3S Enterprise-class USB3.0 PTZ Video Conferencing Camera , positioning for middle and large meeting room video communication



FEATURES

- ◆ Adopted Ambarella ISP, Sony 1/2.8 5MP sensor, output full HD 1080p with 60 frames per second video streaming, to offer you completely high definition, noiseless and crisp, realistic color image with full details
- ◆ using multi-element 12x lossless optical zoom lens, with 72.5 degree wide angle FOV, along with smooth pan&tilt rotation and fast&accurate focus to capture any view in conferencing space

- ◆ USB3.0 Output, Plug-and-Play, standard UVC1.5 protocol enable users to connect camera with PC by a single USB cable
- ◆ compatible with most leading video conferencing software and platform, Zoom.us, Skype4business, Vidyo, Bluejeans, Webex, Google Hangout, Trueconf, Gotomeeting ect, at different operation system Windows, Mac, Android and Linux
- ◆ Standard UVC1.5 protocol enable users to connect camera with PC by a single USB cable
- ◆ FECC (far-end camera control) supported
- ◆ Standard Sony Visca and UVC1.5 protocol, PTZ control and firmware upgrade via RS232 (RS485) and USB port
- ◆ 128 presets supported
- ◆ Support multiple mount way: available to install on desk, monitor, tripod or up-side down in-ceiling



Telecam Technology Co.,Ltd

New Add.: 6F, Building A, Shuanghuan Information Technology Industrial Park, No.8, Baoqing Rd, Longgang District, Shenzhen, 518116, China

TEL: 0086-755-33275155 [Http://www.telycam.com](http://www.telycam.com) www.telecamtech.com

TLC-300-U3S

USB3.0

HD PTZ Video Camera



TECHNICAL SPEC

Sensor	1/2.8 inch high quality 5MP HD CMOS sensor,		
Video System	1920x1080p60/50/30/25, 1280x720p60/50/30/25		
Video Format	YUY2	Lens Zoom	12x optical zoom
Focal length	f=3.92(wide)~47.32mm(tele)	View Angle	6.3° (wide) ~ 72.5° (tele)
SNR	>50dB	Noise Reduction	2D/3D
Minimum Lux	0.1 lux	White Balance	Auto / Manual
Focus	Auto / Manual	Iris	Auto / Manual
Electronic Shutter	Auto / Manual	BLC	Auto / Manual
Pan Rotation Angle	-170° ~ +170°	Tilt Rotation Angle	-35° ~ +90°
Pan Rotation Speed	0°~120°/s	Tilt Rotation Speed	0°~80°/s
Preset	128 presets via RS232, 10 presets via remote controller	Control	RS232/RS485/USB/Remote Controller
Video Port	USB3.0	Input voltage	DC12V

Camera Dimension
220mm×173mm×117mm

Package Dimension
32x30x31cm

Package Content

Camera, Remote Controller,
RS232 cable, USB3.0 cable,
Power Supply

