

V-JOY+/V-JOY

NDI CONTROL KEYBOARD



Key features

● Broad Compatibility

Supports multiple protocols NDI®, VISCA over IP, Serial VISCA, ONVIF, PELCO P/D, Users can control multiple cameras with different protocols with one keyboard, or multiple keyboards controlling one camera through a network interface. It has 7 camera control shortcut keys, to enable up to 255 cameras to be controlled via a keyboard.

● Intuitive and Clear Layout

A high-definition screen to show detailed camera and control status.
PTZF four-dimensional joystick to make smooth control of the camera's all-around rotation, zooming and focus.
Independent layout of numeric and functional areas for clear setup and control.

● Flexible Control

Basic pan/tilt/zoom control, PTZ control speed as well as preset can be easily accomplished. Auto tracking switch and set.
128 preset positions can be set, recalled, and cleared via the numerical button area.
Focus, Iris, Exposure, White balance, WDR, and Backlight compensation can be set and adjusted.

Application



Specification

Camera	V-Joy+	V-Joy
Part NO.	TLC-50TC(NDI)	TLC-50TC
Control Ports	NDI® HX, RS232, RS422, RS485	RJ45, RS232, RS422, RS485
RJ45	Ethernet port, POE (IEEE802.3af)	
RS232	DB9 Male head	
RS422	3.81 Spacing terminal, T+, T-, R+, R-	
RS485	3.81 Spacing terminal, T+, T-	
Control Protocols	NDI®, VISCA Serial, PELCO-P, PELCO-D, VISCA over IP, VISCA TCP, VISCA UDP, ONVIF	
Upgrade Port	Type-C	
LCD Screen	3.12-inch OLED screen, blue light, 256x64 pixel	
Working Power	12V, 1A	
Working Temperature	-10℃~50℃	
Working Humidity	20%~80%	
Storage Temperature	-20℃~60℃	
Storage Humidity	0~90%	
Dimension	320.5mmx156.5mmx118mm	
Net Weight	1.05kg	



Please scan with browser.

Telecam Technology Co.,Ltd

Phone number: +86 755 33275155 E-mail: sales@telycam.com

Add: 6 Floor, Building A, Shuanghuan Information Technology Industrial Park, No.8, Baoqing Rd, Longgang District, Shenzhen, 518116, China